




For installation information please refer to the tooling overview and manuals on our website.
 Pour les conditions de pose, merci de vous référer à la description de l'outil et aux manuels disponibles sur notre site Web.
 Angaben zur Verarbeitung entnehmen Sie bitte der Geräteübersicht und den Betriebsanleitungen auf unserer Website.
 Per informazioni sull'installazione preghiamo consultare i manuali e la panoramica degli attrezzi sul nostro sito web.
 Para ver información sobre máquinas de colocación, consulte nuestra página web, apartados visión general de máquinas y manuales.

English	Français	Deutsch	Italiano	Español
Body: Stainless steel* Natural	Corps: Inox* Brut	Hülse: Edelstahl* Unbehandelt	Corpo: Acciaio inox* Nessuna finitura	Cuerpo: Acero inoxidable* Natural
Stem: Stainless steel** Natural	Tige: Inox** Brut	Dorn: Edelstahl** Unbehandelt	Gambo: Acciaio inox** Nessuna finitura	Vástago: Acero inoxidable** Natural

*: BS 970 302S31 AISI302
 **: A286



CCPQ
Protruding head
Tête bombée / Flachrundkopf /
Testa tonda / Cabeza alomada

CCCQ
Countersunk
Tête fraisée / Senkkopf /
Testa svasata / Cabeza avellanada

Ø nom.	CCPQ			CCCQ		M max.	ØE ref.	kN ²⁾	kN ²⁾	CCPQ ■			CCCQ ■		
	min.	mid. ¹⁾	max.	min.	max.					ØB	D max.	Part No. /ref ■	ØB ±0.2	D ref.	Part No. /ref ■
3.2 (1/8")	1.60	2.36	3.18	3.3	3.4	6.99	1.9	3.11	2.67	6.3 ±0.4	1.1	-04-02	5.74	0.8	
	2.39	3.56	4.75			8.56						-04-03			-04-03
	3.20	4.75	6.35			10.16						-04-04			-04-04
	4.78	6.35	7.92			11.73						-04-05			-04-05
	6.38	7.92	9.53			13.59						-04-06			-04-06
	9.55	11.10	12.70			17.02						-04-08			
4.0 (5/32")	1.57	2.36	3.18	4.1	4.2	7.62	2.4	4.67	4.45	7.9 ±0.5	1.3	-05-02	7.14	1.0	
	2.39	3.56	4.75			9.19						-05-03			
	3.20	4.75	6.35			10.80						-05-04			-05-04
	6.38	7.92	9.53			13.97						-05-06			-05-06
	9.55	11.10	12.70			17.65						-05-08			
4.8 (3/16")	1.57	2.36	3.18	4.9	5.0	8.26	2.9	7.34	5.78	9.5 ±0.5	1.5	-06-02	8.74	1.3	
	3.20	4.75	6.35			11.43						-06-04			-06-04
	4.78	6.35	7.92			13.00						-06-05			
	6.38	7.92	9.53			14.61						-06-06			-06-06
	9.55	11.10	12.70			17.78						-06-08			-06-08
6.4 (1/4")	3.20	4.75	6.35	6.5	6.6	12.70	3.8	10.90	10.00	12.7 ±0.7	2.0	-08-04	11.9	1.8	-08-04
	6.38	7.92	9.53			15.88						-08-06			-08-06
	9.55	11.10	12.70			19.05						-08-08			-08-08

all dimensions in mm / en millimètre / alle Maße in mm / in millimetri / en milímetros

- Mandrels break flush with rivet head at mid. grip
 La tige rompt affleurante à la tête du rivet en milieu de plage de serrage
 Bei mittlerem Klemmbereich (mid.) reißt der Dorn bündig mit dem Nietkopf ab
 Q Rivet rottura del chiodo a livello della testa del rivetto per grip medio
 El punto de rotura del Q Rivet es a ras con la cabeza del remache en su grip intermedio
- typical values / valeurs moyennes / typische Werte / Valori tipici / valores típicos