




For installation information please refer to the tooling overview and manuals on our website.  
 Pour les conditions de pose, merci de vous référer à la description de l'outil et aux manuels disponibles sur notre site Web.  
 Angaben zur Verarbeitung entnehmen Sie bitte der Geräteübersicht und den Betriebsanleitungen auf unserer Website.  
 Per informazioni sull'installazione preghiamo consultare i manuali e la panoramica degli attrezzi sul nostro sito web.  
 Para ver información sobre máquinas de colocación, consulte nuestra página web, apartados visión general de máquinas y manuales.

English	Français	Deutsch	Italiano	Español
90° Countersunk	90° Tête fraisée	90° Senkkopf	90° Testa svasata	90° Cabeza avellanada
Closed end	Borgne	Geschlossen	Fondo cieco	Fondo cerrado
Aluminium alloy* (2.5 % Mg) Natural	Alliage d'aluminium* (2.5% Mg) Brut	Aluminium* (2.5 % Mg) Blank	Lega di alluminio* (2.5% Mg) Nessuna finitura	Aluminio* (2.5% Mg) Natural

\* : AA 5052, DIN 1725, AlMg2.5, Werkstoff 3.3523



Thread filetage / Gewinde / filetto / rosca	e (grip)		Thread Pitch	øA max.	øB +0/-0.4	D +0.3/-0.1	øJ max.	M ± 0.35	P max.	Part No/ref
	min.	max.								
M4 x 0.7	1.70	3.50	6.10	6.00	9.00	1.50	8.10	15.50	10.80	0GM57-00435
	3.50	5.00						17.00		0GM57-00450
M5 x 0.8	1.70	4.00	7.10	7.00	10.00	1.50	9.60	18.00	14.30	0GM57-00540
	4.00	6.50						20.50		0GM57-00565
M6 x 1.0	1.70	4.50	9.10	9.00	12.00	1.50	12.10	22.00	17.50	0GM57-00645
	4.50	6.50						24.00		0GM57-00665
M8 x 1.25	1.70	4.50	11.10	11.00	14.00	1.50	14.50	25.00	19.00	0GM57-00845
	4.50	6.50						28.00		0GM57-00865

all dimensions in mm / en millimètres / alle Maße in mm / in millimetri / en milímetros

Thread filetage / Gewinde / filetto / rosca	 Recommended max. torque Nm max.	 Pull-out kN	 Torque-to-turn Nm min.	 Push-out kN
	M4 x 0.7	4.0	4.7	1.7
M5 x 0.8	5.3	6.3	2.2	2.6
M6 x 1.0	10.8	10.1	4.7	3.4
M8 x 1.25	23.0	11.7	7.8	3.7