

Vertical Riveting Tool 07535-00012

Fixed Arm Workstation for Avdel Speed Fasteners

This tool can place the entire range of Avdel Speed Fastening® Systems and is used for "Top-Down" riveting requirements. The tool is foot pedal operated, leaving both hands of the operator free to position the workpiece.

Rapid assembly makes it cost-effective, even with small batch sizes. Simple to operate, high mobility and easy integration into the production process are the main features. Time-consuming training of an operator is not necessary. The hydraulic riveting unit provides a smooth riveting, ideal for sensitive components.

Features and Benefits

- Tool supported on a fixed arm
- Foot pedal control, leaving both hands free to position the workpiece
- Easy alignment of workpiece
- Height and throat adjustable arm to meet the operator's precise ergonomic needs
- Bolts provided for base plate bench mounting



Specifications

Max. clearance height	250 mm
Stroke min.	30.0 mm
Pull force at 5.5 bar	3.89 kN
Cycle Time approx.	1.0 sec
Noise level	< 70 dB(A)
Air pressure supply	5 - 7 bar
Air consumption at 5.1 bar	2,6 l free air / sets
Intensifier ratio	32:1
Part-No. basic tool	07535-00012*
*nose equipment has to be ordered separately	

Placing Capability

The 7535 placing tool can place the whole range of Speed Fastening® fasteners from diameter 2.4 mm to 6.4 mm.

For detailed information on placing capability and nose equipment please refer to the tool manual or contact your local STANLEY Engineered Fastening representative.



Dimensions (in mm)

